

# WELMOUNT™ 80000/90000 SERIES

Welmount™ 80000 and 90000 double-sided foam tapes have been designed to meet the most demanding industrial applications. Welmount™ cross-linked polyethylene foam provides good sealing characteristics and is perfect for bonding to most smooth or irregular surfaces. The perfect mounting tape for all of your safety signage and mounting requirements.



© Jessup 2006

FEATURES	BENEFITS
Quality Raw Materials	The closed cell polyethylene foam is flexible and conformable. This allows Welmount™ foam tapes to bond rigid materials to uneven surfaces.
Available	Welmount™ foam tapes are available in rolls from 1/4" to 27" wide, custom sheets and custom die cut parts to meet your exact specifications. A variety of adhesives are available to meet your specific substrate and temperature requirements.

## TECHNICAL DATA

Surface Compatibility:	Most clean, dry, oil free surfaces
Application Temperature:	Apply when above 50° F
Storage Life:	1 Year @ 72° F/50% relative humidity
Material Thickness:	1/32", 1/16", 1/8"
Standard Sizes:	Roll Widths: from 1/4" to 27" Custom die cuts and other sizes available on request
Colors Available:	White and Black
Product Description:	A closed cell cross-linked polyethylene foam utilizes either a synthetic polymer based adhesive or a general purpose acrylic based adhesive.  80000 Series – Synthetic polymer based adhesive system on two sides.  90000 Series – General purpose acrylic based adhesive system on two sides.  Custom adhesives and combinations available upon request.